Argos

Entrance control / Sliding gate

The Heras Argos gate combines optimum flexibility and security. This is a perfect example of how a swing gate has been developed into a sliding gate for welded mesh panel fences and chain link fences. Strong and clever, this smoothly running gate is made from high-quality aluminium. The narrow mesh width of the welded mesh panel makes the gate difficult to climb. Argos is delivered completely assembled. As standard, the welded mesh panel comes with a protective coating. The clear width varies from 6000 to 7000 mm on a single-leaf gate. All versions are operated electrically as standard. The Argos gate is highly suitable for integration with welded mesh and chain link fencing.

- **Sliding gates**
- **Easy to install**
- **Fully assembled**

Drawings

Lightweight to handle


Rounded and safe angles

Various options

Smart and robust

Technical specifications (dimensions in mm)

Table of dimensions	Height	Clear width	Total room required
Argos 60/180	1800	6000	13731
Argos 60/200	2000	6000	13731
Argos 70/180	1800	7000	15929
Argos 70/200	2000	7000	15929

Colour schemes

- Option 1: Welded mesh panel, coated RAL 9006 with a blank aluminium frame with RAL 5016 striping
- Option 2: Gate fully RAL 6005 coated with RAL 9010 striping
- Other RAL colours are available upon request.

Standard configuration

- All versions are operated electrically as standard.
- The Argos gate is suitable for integration with welded mesh and chain link fencing.
- Fully assembled
- Mesh width 50 x 200 mm
- Safe, rounded corners
- Gate height 1800 + 2000 mm
- Clear width 6000 / 7000 mm
- Electrical operation

Coating

Galvanised and aluminum parts are pre-treated before coating. Electrostatic powder-coating is then applied, after which the coated materials are cured in an oven (210 °C) to create a durable coating with an average thickness of 80 µm and a hardness of 80 buchholz.

Options

- Serrated strip
- Electrical flash light
- Infrared
- Flood light
- Extra remote control

Heras reserves the right to make product changes without prior notice. We do not accept any responsibility for mistakes, inaccuracies and/or printing errors. INEN_3B1A_1.1

Hekdam 1 | Postbus 30 | 5688 ZG Oirschot | The Netherlands
+31 499 551 523 | export@heras.com | **export.heras.com**